

Eaton 170M3815D

Catalog Number: 170M3815D

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 200A, 200 kAIC, Combination fuse status indicator, Fuse, Din 43-620 blade end X Din 43-620 blade end, Class aR

General specifications

| | |
|---------------------------------------------------|-----------------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series high speed square body fuse | 170M3815D |
| | UPC |
| | 051712334037 |
| EAN | Product Length/Depth |
| 5027590450300 | 135 mm |
| Product Height | Product Width |
| 64 mm | 40 mm |
| Product Weight | Compliances |
| 418.8333333 g | CE Marked |
| | RoHS Compliant |
| Certifications | |
| UL Recognized | |
| IEC Rated | |



Especificaciones del producto

Recursos

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

200 A

Breaking capacity

200 kA

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1

Rated voltage AC

690 V

Current type

AC

Class

Class aR

Clearing (I₂T)

16500 at 660 V

Watt losses

12.5 W

Fuse shape

Square body, knife blade contacts

Pre arc (I₂T)

2300

Color

None

Interrupt rating

200 kAIC

Fitted with:

Dual indicator

Connection

Din 43-620 blade end x Din 43-620 blade end

Construction size

1

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43620

Bladed

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Todos los
derechos reservados.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)